

4 CHANEL TEMPERATURE CONTROLLER & INDICATOR

Sensor - J | K | RTD



MODEL	DTC 9644	DTI 9644
FRAME	96X96	96X96
PANEL	92X92	92X92
DISPLAY	4 Digit 0.56" RED 4 Digit 0.39" GREEN	4 Digit 0.56" RED 4 Digit 0.39" GREEN

INPUT

Sensor
Range

J & K OR RTD & RTD.1 2W/3W (Configurable)
J(0°C to 400°C & 0°C to (600°C), K(0°C to 1200°C),
PT-100 2W/3W(0°C to 400°C, -50.0°C to 200.0°C)

Stage

9999 Second / Minute / Hour

OUTPUT

Control Output
Capacity
SSR

RELAY
1CO, 7 Amp, 230 Volt AC
12V DC Approximately

SPECIFICATIONS

Supply Voltage
Set Point
Control Mode
Operating Mode
Accuracy
Enclosure Material
Operating Temperature
Relative Humidity

230v AC, $\pm 10\%$, 50Hz
4 Set Point
ON-OFF
HEAT & COOL Mode
 $\pm 1\%$ of FSD
Polycarbonate + ABS Plastic
0°C - 55°C
Upto 95% RH Non Condensing